

Data Sheet Fujitsu Mainboard D3441-S μ ATX

Industrial Series

Available from
04/2016

Powered by the Intel® Q170 Express Chipset supporting DDR4 2133 SDRAM Memory and 6th generation Intel® Core™ i3 / i5 / i7 Processors (Socket LGA1151)
Designed for 24/7 continuous operation and enhanced operating temperature range



Chipset:

Intel® Q170 Express Chipset

Processors:

Intel® Core™ i7 / i5 / i3 – (6th gen.) processor series

Intel® Pentium® / Celeron® processor series



Memory:

DDR4 2133 SDRAM (UDIMM)

Product Features:

Intel® iAMT 11.0 / vPro 2015

Onboard support for Mini-PCI Express and mSATA



Intel® HD Graphics; PCI Express Gen3

Multichannel Audio & Dual Intel GbE LAN onboard

USB 2.0/3.0 and USB 2.0 socket (stick) onboard

Trusted Platform Module V2.0 (Infineon) onboard

HW Watchdog onboard



Features and benefits

Board Size	µATX: 9.6" x 9.6" (243.8 x 243.8 mm)
Chipset	Intel® Q170 Express Chipset
Memory	4 DIMM Sockets DDR4, max. 64GB, Dual Channel, 2133MHz (CL15), UDIMM, 1.2V/2.5V, 288-pin, non-ECC. Effective memory speed depends on installed processor
Processor	Intel® Core™ i7 / i5 / i3 – (6th generation) processor series Intel® Pentium® / Celeron® processor series Socket LGA1151, max. 65W TDP
Power Specification	ATX- 24 Pin or ATX- 20 Pin + 4 Pin (12V) Power Connector required Support for Soft-Off Power Supplies 12V and 3.3V Supply Voltage on PCIe Slots 3.3V Auxiliary Supply Voltage on PCIe Slots (Wake-Up Function) On board CPU Voltage Regulator, 5V / 2A Auxiliary Power required for USB Wake-Up from Save-to-RAM, Save-to-Disk

Power Supply Requirements
for onboard components (worst case incl. processor & memory; w/o USB devices; w/o PCIe cards; w/o SATA drives; w/o mSATA / mPCIe;)

Source	Voltage	Min. PS Load	Max. Voltage Tolerance	Mainboard Capacitive Load	Max. Mainboard Current
Main Power Supply	+ 12V	0.05A	± 5 %	5.000µF	8A/12A ¹⁾
	- 12V	0A	± 10 %	470µF	0.3A
	+ 5V	0.2A	± 5 %	3.000µF	6.0A
	+ 3.3V	0A	± 5 %	3.000µF	0.5A
Aux. Power	+ 5Vaux	0A	+ 5 % / -3%	3.000µF	2.5A

1) Max. Cont. Current = 8A; max. Surge Current = 10A (< 100sec) / 12A (< 10ms)

BIOS
AMI Aptio 5.x (UEFI) BIOS
modified and adapted by Fujitsu Technology Solutions; Recovery BIOS, SM-BIOS (DMI), BIOS and CPU Microcode Update, Quick Boot, Logo Boot, Quiet Boot, Plug & Play, Automatic DRAM and PCIe Configuration, BIOS Support for S.M.A.R.T., Advanced Power Management, ACPI S3/S4, Wake on time from S5.
Boot support for M.2 Carrierboard D3352-A1 (PCIe-based SSD modules, AHCI/NVME). BIOS integrated HW Diagnostic Tool

Security Features
Recovery BIOS, System and BIOS Password, Boot Sequence Control, Serial-/ Parallel-/ USB- Port Access, Boot Sector Virus Warning, Write Protection for Flash BIOS, EraseDisk (BIOS Feature); TPM V2.0 (Infineon SLB 9665; TCG compliant).

Special Features	Description
Silent Fan	Independent temperature related processor fan and system fan supervision and control
System Guard	View and adjust Silent Fan features
Silent Drives	Noise reduction for optical and hard disk drives
Recovery BIOS	Restores a corrupted BIOS
Desk Update	Simple driver update with Driver&Utilities DVD
Multi Boot	Comfortable boot from any boot device
HDD Password	Access protection for disk drives
CSA / UL / FCC certified	cCSAus 60950-1/ FCC-B (planned)

Supported / Released Operating Systems		
OS	"Runnable"	"Tested/Released by Fujitsu"
MS Windows XP	--	--
MS Windows 7-32	X	X
MS Windows 7-64	X	X
MS Windows 8.1-64	X	X
MS Windows 10-64	X	X
MS Server 2008 R2	X	basic capability approved
MS Server 2012 R2	X	basic capability approved
MS Server 2016	planned	planned
Linux-32	X	
Linux-64	X	

Designed for Industrial Applications
Longlife components Designed for 24/7 use in industrial applications
ENIG-plated PCB (tbd) Improved durability of PCB surface
Revision control Strict control and pre-announcement
Extended lifecycle Mainboard available for more than four years
Industrial grade EMI immunity
Enhanced operating temperature range (0°C-60°C) ¹⁾

Graphics
Intel® HD Graphics (depends on installed processor), DX12

Audio
Realtek ALC671, 5.1-channel, High Definition Audio Codec


LAN
Intel i219LM & i210AT with 10/100/1000 MBit/s, iAMT 11 / vPro Support, Wake-on-LAN (WoL) by interesting Packets, Link Status Change and Magic Packet™, PXE Support, BIOS MAC Address Display, Teaming Support

Drives
1 x mSATA (half-/fullsize), SATA-III (shared with one SATA port), incl. USB2.0 6 x SATA-III; NCQ, AHCI, RAID 0/1/5/10


Features	D3441-S
Chipset / Board Size	iQ170 / µATX
VGA ²⁾ / DVI-I / DVI-D / DP V1.2 / 2 nd DP V1.2 / LVDS	- / - / ✓ / ✓ / ✓ / ✓ / -
Stereo Audio / 5.1 Multichannel Audio	- / ✓
Buzzer / int. Speaker Support	✓ / ✓
Dual LAN Gbit / 100 Mbit / 10 Mbit / WoL / LAN Boot	✓ / ✓ / ✓ / ✓ / ✓ / ✓
iAMT 11.0 vPro / Intel Standard Manageability / DASH V1.1	✓ / ✓ / ✓ / ✓
SATA / ATA / RAID / eSATA-Support / mSATA / M.2 SSD ³⁾	✓ / - / ✓ / ✓ / ✓ / ✓ / -
FireWire™ / USB 2.0 / USB 3.0	- / ✓ / ✓ / ✓
FAN monitored & controlled PSU ⁴⁾ / CPU / AUX1 / AUX2 / Aux3	✓ / ✓ / ✓ / ✓ / ✓ / ✓
TEMP monitored CPU / onboard sensors / external sensor	✓ / ✓ / ✓ / -
Special Features	
Silent Fan / Silent Fan LT / System Guard / Silent Drives	✓ / - / ✓ / ✓ / ✓
Recovery BIOS / Desk Update / Multi Boot	✓ / ✓ / ✓ / ✓
HDD Password / HDD Encryption / EraseDisk / TPM	✓ / - / ✓ / ✓ / ✓
BIOS POST Watchdog / BIOS Boot Watchdog / OS HW Watchdog	✓ / ✓ / ✓ / ✓
Logo Boot Option / Intel On Screen Branding	✓ / ✓
High Efficiency Core Voltage Regulator Design	✓
Operating Mode 24-7 / 8-5 (hrs per day - days per week)	✓ / -
Mainboard operating temperature range (chassis inside)	0°C - 60°C
Internal Connectors	
DIMM Sockets (DDR4-2133)	4
PCI Express x16 (16 Lanes, Gen3) / x16 (4 Lanes, Gen3)	1 / 1
PCI Express x8 (4 Lanes, Gen3) / x8 (1 Lane Gen3)	1 / 1
PCI Slots (32Bit, 33 MHz, Rev. 2.3) / Mini-PCI Express ⁵⁾	- / 1
SATA-600 / SATA-300 / mSATA ⁵⁾ / M.2 SSD	6 / - / 1 / -
S/PDIF (digital Audio) OUT / IN	1 / -
Frontpanel Audio (9-Pin, HD Audio & Legacy Audio AC97)	1
USB 2.0 channels / USB 3.0 channels / USB Stick (2.0)	2 / 2 / 1
Serial (COM2, RS232)	1
FAN PSU ⁴⁾ / CPU / AUX1 / AUX2 ⁷⁾ / Aux3	1 / 1 / 1 / 1 / 1
Intrusion (Case Open) / GPIO (8Bit) / SMBus (Case Temp.)	1 / 1 / -
Parallel Port Pin Connector ⁶⁾	1
ATX Power Supply (24 pin + 4 pin) / 12V-only Power Supply	✓ / -
External Connectors	
VGA Sub D ²⁾ / DVI-I / DVI-D / DisplayPort V1.2	- / - / 1 / 2
Audio Mic. In / Line in / Line out (or driver configuration)	1 / 1 / 1
LAN (RJ-45)	2
PS/2 Mouse / Keyboard	1 / 1
USB 2.0 / USB 3.0	4 / 4
Serial (COM1, RS232)	1
Parallel (EPP/ECP) ⁶⁾	-

- 1) Forced cooling required, see technical documentation for detailed requirements
- 2) VGA possible via optional converter board D3453 or DP-VGA-converter (dongle)
- 3) M.2 support possible via D3352 M.2 Carrier Board (for PCIe/AHCI-based SSD modules)
- 4) Not supported by standard Power Supplies
- 5) mSATA / Mini-PCI Express = shared socket (halfsize / fullsize support)
- 6) External parallel port possible via optional connector cable
Note: Intel limitation → ECP-DMA-Mode no longer supported
- 7) One fan useable in PWM- or 3-pin mode (BIOS Option)

External Connectors



Connector / Socket Diagram



Further industrial products offered by Fujitsu

- Connectors
- KVM Switches
- Relays
- Touch Panels
- Thermal Printers
- Wireless Modules



24 Volt Kiosk Printers



Multi-Input Touch Panels

Contact:

Fujitsu Components Europe, B.V.
 Tel.: +31 (0)23 556 0910
 Fax: +31 (0)23 556 0950
 Website: emea.fujitsu.com/components
 Address: Diamantlaan 25
 2132 WV Hoofddorp
 Netherlands

More information

Fujitsu products, solutions & services

Products

www.fujitsu.com/global/products/
In addition to the Fujitsu [Product name], Fujitsu offers a full portfolio of other computing products.

Computing products

- Storage systems: ETERNUS
- Server: PRIMERGY, PRIMEQUEST, Fujitsu SPARC M10, BS2000/OSD Mainframe
- Client Computing Devices: LIFEBOOK, STYLISTIC, ESPRIMO, FUTRO, CELSIUS
- Peripherals: Fujitsu Displays, Accessories
- Software
- Network

Product Support Services with different service levels agreements are recommended to safeguard each product and ensure smooth IT operation.

Solutions

<http://www.fujitsu.com/global/solutions>
The Fujitsu solutions combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships. Fujitsu's Solutions include parts of one or more activity groups (e.g., planning, implementation, support, management, and training services) and are designed to solve a specific business need.

Infrastructure Solutions are customer offerings created by bringing Fujitsu's best products, services and technologies together with those from partners to deliver benefit to our customers' businesses.

Industry Solutions are tailored to meet the needs of specific verticals.

Business and Technology Solutions provide a variety of technologies developed to tackle specific business issues such as security and sustainability, across many verticals.

Services

www.fujitsu.com/global/services/
Several customizable Fujitsu Service offerings ensure that IT makes a real difference and delivers true business value. We do this by leveraging our extensive experience in managing large, complex, transformational IT programs to help clients in planning, delivering and operating IT services in a challenging and changing business environment.

Application Services support the development, integration, testing, deployment and on-going management of both custom developed and packaged applications. The services focus on delivering business and productivity improvements for organizations.

Business Services respond to the challenge of planning, delivering and operating IT in a complex and changing IT environment.

Managed Infrastructure Services enable customers to deliver the optimal IT environment to meet their needs – achieving high levels of IT service quality and performance for data center and end user environments.

Fujitsu green policy innovation

www.fujitsu.com/global/about/environment/
Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at:



More information

Learn more about Fujitsu, please contact your Fujitsu sales representative, Fujitsu business partner, or visit our website.
www.fujitsu.com/fts/mainboards/

Copyright

© 2015 Fujitsu Technology Solutions GmbH
Fujitsu and the Fujitsu logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries.

Intel Chipset H150 and Intel Core i7 / i5 / i3 are trademarks or registered trademarks of Intel Corporation in America and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners.

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Disclaimer

Technical data subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
OEM Mainboard Sales
Email: oem-sales@ts.fujitsu.com

Website: <http://ts.fujitsu.com>
2016-04-18