


LCM PIN ASSIGNMENT	
1.	VCOM
2.	VDDIN
3.	VDDIN
4.	GND
5.	RST
6.	NC
7.	GND
8.	MIPI_ON
9.	MIPI_OP
10.	GND
11.	MIPI_1N
12.	MIPI_1P
13.	GND
14.	MIPI_CKN
15.	MIPI_CKP
16.	GND
17.	MIPI_2N
18.	MIPI_2P
19.	GND
20.	MIPI_3N
21.	MIPI_3P
22.	GND
23.	NC
24.	NC
25.	GND
26.	NC
27.	PWM0
28.	NC
29.	VCL
30.	GND
31.	LED-
32.	LED-
33.	NC
34.	NC
35.	AVEE
36.	NC
37.	NC
38.	AVDD
39.	LED+
40.	LED+

CTP PIN ASSIGNMENT	
1.	VDD
2.	GND
3.	GND
4.	SCL
5.	SDA
6.	GND
7.	INT
8.	RESET

NOTES:

1. DISPLAY TYPE: 7.0" TFT, TRANSMISSIVE
2. VIEWING DIRECTION : U/L/D/R 80/80/80/80
3. Driver IC : N/A
4. CTP Driver IC : GT928 or EQU
5. Top : -20° C ~ 70° C, Tst : -30° C ~ 80° C
6. GENERAL TOLERANCE: ±0.2
7. RoHS Complicant

LED CIRCUIT DIAGRAM:



DLC Display Co., Limited
www.dlcdisplay.com

DRAWN BY:	TITLE: DLC0695DIG-T-5	
CHECKED BY:	DWG NO:	SCALE:
APPROVED BY:		UNIT: mm
CONFIRMED BY:	DWG NAME:	SHEET NO: OF