

Data Sheet

FUJITSU Mainboard D3544-S Mini-STX

Industrial Series

Intel® embedded Gemini Lake SoC (System on Chip, 10W TDP) for DDR4 2400 SDRAM Memory
Enhanced operating temperature range from 0°C to 60°C



Processors (SoC):


Intel® Celeron® Processor J4005 (DC @2.0GHz / 2.7GHz), integrated Intel® UHD Graphics 600 (12EUs @700MHz)
Intel® Celeron® Processor J4105 (QC @1.5GHz / 2.5GHz), integrated Intel® UHD Graphics 600 (12EUs @750MHz)
Intel® Pentium® Silver Processor J5005 (QC @1.5GHz / 2.8GHz), integrated Intel® UHD Graphics 605 (18EUs @800MHz)
10W TDP

Memory:


DDR4 2400 SDRAM (SO-DIMM)

Product Features:

Intel® UHD Graphics 600/605 (within SoC)
2x DisplayPort V1.2a
Dual Channel LVDS (24Bit) and eDP V1.4 onboard
8 Bit GPIO & HD Audio onboard
USB 2.0 and USB 3.1 (gen1) onboard
2x SATA III
Onboard support for M.2 SSD (SATA/PCIe)
Onboard support for M.2 WLAN/Bluetooth module
Dual GbE LAN onboard
Intel® integrated TPM V2.0 onboard
WideRange internal/external DC Input (8V - 24V)
HW Watchdog onboard
RS-232/485/422 support onboard



(upon request)



Features and benefits

Board Size Mini-STX: 5.5" x 5.8" (140 x 148 mm)

Mainboard Versions

	Processor (SoC)	Graphics	Memory	Graphics
D3544-S1	Intel® Celeron® J4005 (Dual Core) 2.0GHz / 2.7GHz ¹⁾	Intel® UHD 600 12EUs; max. 8GB 250MHz / 700MHz ²⁾	DDR4 / 2400 one socket max. 16GB	2 x DP V1.2 max. 4096 x 2160 @60Hz
D3544-S2	Intel® Celeron® J4105 (Quad Core) 1.5GHz / 2.5GHz ¹⁾	Intel® UHD 600 12EUs; max. 8GB 250MHz / 750MHz ²⁾		1 x eDP V1.4 2 lanes max. 1920 x 1200
D3544-S3	Intel® Pentium® Silver J5005 (Quad Core) 1.5GHz / 2.8GHz ¹⁾	Intel® UHD 605 18EUs; max. 8GB 250MHz / 800MHz ²⁾		1 x LVDS 24Bit Dual Channel max. 1920 x 1200 max. 3 x independent display

1) CPU Base Frequency / Burst Frequency 2) Graphics Base Frequency / max. Dynamic Frequency

Memory 1 x SO DIMM Socket (1.2V), max. 16GB,
DDR4 - 2400 (CL17) / 2133 (CL15) SDRAM, unbuffered, non-ECC

Power Specification External DC Input 8V-24V (5A max. / 100W max.)
Internal DC Input 8V-24V (8A max. / 100W max.)
Onboard SoC and system voltage regulators (high efficiency)

Power Supply Requirements

Source	Voltage Range	Min. PSU Load	Max. Voltage Tolerance	typ. Mainboard Input Power ¹⁾	max. Mainboard Input Power ²⁾
DC-IN (wide range)	8-24V	0A	± 5 %	5W - 15W	100W

1) Mainboard incl. Memory and M.2 SATA SSD (MS Windows 10 Idle Mode / Full Load)

2) Mainboard incl. Memory, M.2 SATA SSD, any USB Devices, any LVDS / eDP devices, any SATA devices
See TechNotes document for detailed power requirements

BIOS AMI Aptio 5.x (UEFI) BIOS
modified and adapted by Fujitsu Technology Solutions; Recovery BIOS, SM-BIOS (DMI), BIOS and CPU Microcode Update, Quick Boot, Logo Boot, Quiet Boot, Plug & Play, Automatic DRAM Configuration, BIOS Support for S.M.A.R.T., Advanced Power Management, ACPI S3/S4, Wake on time from S5. Boot support for M.2 SSD (AHCI / NVME)
BIOS integrated HW Diagnostic Tool, Watchdog Support
No legacy OS support, no MBR installation (UEFI only due to Intel restrictions)

Security Features Recovery BIOS, System and BIOS Password, Boot Sequence Control, Serial- / USB- Port Access Protection, Boot Sector Virus Warning, Write Protection for Flash BIOS, EraseDisk (BIOS Feature), Intel integrated TPM V2.0


Special Features	Silent Fan System Guard Silent Drives Recovery BIOS Desk Update Multi Boot HDD Password Always On Never Off CSA / UL Compliance FCC Compliance	Independent temperature related processor fan supervision View Silent Fan features Noise reduction for optical and hard disk drives Restores a corrupted BIOS Simple driver update with Driver & Utilities DVD Comfortable boot from any boot device Access protection for disk drives Reliable power-on whenever voltage is connected Option to prevent the system from being shut down Upon request: TÜVus acc. IEC62368-1 FCC-B verified	
Operating Systems	OS	"Runnable"	"Tested/Released by Fujitsu"
	MS Windows 10-64 RS1 ¹	X	--
	MS Windows 10-64 RS2 ¹	X	--
	MS Windows 10-64 RS3	X	X (recommended!)
	Linux-64	X	functional test planned
	Important Note: Legacy OS / MBR installation (DOS, MS Windows 7, ...) is not supported due to Intel restrictions		
Designed for 24 / 7 use	Longlife components for 24 / 7 use (0°C – 60°C) in industrial applications Revision control & Extended Lifecycle (min. 5 years + 1 year eXtended LifeCycle option)		
Graphics	Integrated Intel® UHD Graphics 600/605 2 x DisplayPort V1.2a / 1 x embedded DisplayPort (eDP) 1.4 / 1 x Dual-Channel 24bit LVDS Supports up to 3 x independent display Following max. display combinations are supported: 2 x DisplayPort (DP, external) + 1 x LVDS (internal) 2 x DisplayPort (DP, external) + 1 x embedded DisplayPort (eDP, internal) Note: Simultaneous use of LVDS and eDP is not supported		
Audio	Realtek ALC671 5.1-channel, High Definition Audio Codec		
LAN	1 x Intel i210 with 10/100/1000MBit/s, Wake-on-LAN (WoL) by interesting Packets, Link Status Change and Magic Packet™, PXE and iSCSI supported, BIOS MAC Address Display 1 x Realtek RTL8111G with 10/100/1000 MBit/s, Wake-on-LAN (WoL) by interesting Packets, Link Status Change and Magic Packet™, PXE support, BIOS MAC Address Display		
Drives / Modules	2 x Serial ATA (SATA) III 600 Interface (up to 6Gbit/s), NCQ, AHCI; 1 x M.2 Key B socket (2242 / 2260 / 2280) for following applications: <ul style="list-style-type: none"> SATA based M.2 SSD modules (recommended for best M.2 SSD performance) PCIe based M.2 SSD modules (one PCI lane) Specific M.2 PCIe-based extension modules like LAN, SATA, COM, etc. Boot support: AHCI / NVME Notes: M.2 (SATA mode only) is shared with SATA port 1 Simultaneous use of M.2 2280 modules and M.2 2230 (WLAN/Bluetooth) possible!		

¹ Long-term driver update support for RS1 (LTSB) and RS2 is not guaranteed by Intel


WLAN / Bluetooth	1 x M.2 Key E socket (WLAN / Bluetooth), mechanical support for 2230 Supports M.2 modules with PCIe x1 (Gen2) and / or USB 2.0 interface <u>Note: Simultaneous use of M.2 2280 modules and M.2 2230 (WLAN/Bluetooth) possible!</u>	
LVDS	LVDS Controller Realtek RTD2136R (DisplayPort to LVDS converter)	
Features D3544-S (Mini-STX)	Chipset	Intel Gemini Lake SoC
	DP V1.2a / 2 nd DP V1.2a / LVDS / eDP V1.4 / HDMI / DVI / VGA	✓ / ✓ / ✓ / ✓ / ✓ / - / - / - / -
	Buzzer / int. Speaker Support (mono) ² / 5.1 Multichannel Audio	✓ / ✓ / ✓ / ✓
	LAN Gbit / 100 Mbit / 10 Mbit / WoL / PXE / M.2 2230 WLAN-BT	✓ / ✓ / ✓ / ✓ / ✓ / ✓ / ✓ / ✓
	iAMT-vPro / Intel Standard Manageability / DASH V1.1	- / - / -
	SATA / M.2 (SATA) / M.2 PCIe (1 lane) / eSATA-Support / RAID / mSATA	✓ / ✓ / ✓ / ✓ / ✓ / ✓ / - / -
	USB 2.0 / USB 3.1 (gen1) / FireWire™	✓ / ✓ / -
	FAN monitored & controlled PSU / CPU / AUX1 / AUX2	- / ✓ / - / -
	TEMP monitored CPU / onboard sensors / external sensor	✓ / ✓ / -
Special Features D3544-S	COM interface support for RS-232 / RS-485 / RS-422	✓
	Silent Fan / System Guard / Silent Drives	✓ / ✓ / ✓ / ✓
	Recovery BIOS / Desk Update / Multi Boot	✓ / ✓ / ✓ / ✓
	HDD Password / EraseDisk ³ / TPM V1.2 / TPM V2.0	✓ / ✓ / - / - / ✓
	Logo Boot Option / Intel On Screen Branding	✓ / ✓
	BIOS POST- / BIOS Boot- / OS- HW Watchdog	✓ / ✓ / ✓ / ✓
	Operating Mode 24-7 / 8-5 (hrs per day - days per week)	✓ / -
	Mainboard operating temperature range (chassis inside) ⁴	0°C – 60°C
Internal Connectors D3544-S	SO DIMM Sockets (DDR4 2400)	1
	SATA-600 / M.2 SSD ⁵ / M.2 WLAN-BT / mSATA	2 / 1 / 1 / -
	Front Panel Audio (9-Pin, HD Audio) / SP-DIF Out (Digital Audio)	1 / 1
	USB 2.0 pin header (provides 1 USB channel) / USB Stick socket	1 / -
	USB 3.1/gen1 pin header (provides 2 USB channels) ⁶	1
	Serial COM1 (RS-232 / -422 / -485; pin header 2mm pitch) ⁷	1
	Serial COM2 (RS-232; specific connector) ⁸ / Parallel Port header	planned / -
	LVDS / LVDS Backlight / Embedded DisplayPort	1 / 1 / 1
	FAN PSU / CPU (PWM) / AUX1 (PWM)	- / 1 / -
	Intrusion (Case Open) / GPIO (8Bit) / SMBus (Case Temp.)	1 / 1 / -
	Mono Speaker header / Stereo Speaker header / Digital MIC header	1 / - / -
	Front Panel (Power Switch, Reset Switch, LEDs, Intel 10 pin header)	1
	SATA Drive Power Connector (5V/12V) / DC-In Connector 8-324 (4 pin)	1 / 1
External Connectors D3544-S	DisplayPort V1.2a / HDMI / DVI / VGA	2 / - / - / -
	Audio Mic. In / Line in / Line out (or driver configuration)	1 / - / 1
	LAN (RJ-45) / PS-2 Keyboard / PS-2 Mouse	2 / - / -
	USB 2.0 / USB 3.1 gen1	4 / 2
	DC-In connector (external input) 8-24V @ 5A max.	1

² Mono speaker support; max. 2.2W @4Ω / 1.3W @8Ω³ BIOS feature; License included⁴ Forced cooling required for high operating temperature range. See TechNotes document for details⁵ SATA-based M.2 SSD is shared with SATA port 1; simultaneous use of M.2 2280 module and M.2 2230 module (WLAN/Bluetooth) possible⁶ USB3 connector includes separate USB2.0 signal pins (2 channels)⁷ RS-232 / RS-422 / RS-485; pin header 2mm pitch. See TechNotes document for details⁸ RS-232; reduced feature set; specific software driver support (mandatory!) currently under investigation; specific connector cable (incl. RS-232 line driver) required. See TechNotes document for details

External Connectors




Connector / Socket Diagram



- 1) Onboard power button (push button) and power LED are designed for usage in Fujitsu STX chassis kit
- 2) Optional speaker kit available upon request for Fujitsu STX chassis kit
- 3) eDP (embedded DisplayPort) connector located at bottom side
- 4) SATA Port1 shared with SATA-based M.2 SSD
- 5) Optional USB Type-C extension cable (USB 3.1/gen1) planned for Fujitsu STX chassis kit
- 6) Optional COM 1 cable for Fujitsu STX chassis kit planned
COM2 port: Reduced feature set; SW driver support currently under investigation.
Requires specific cable with integrated line driver
- 7) Supports one USB2.0 channel only (→Bottom pin header row = 4 pins + key useable)

Accessories

	(Ordercode)
Mini-STX Chassis Kit for D3544-S	F5000-J4
AC Adapter 19V / 40W	F5000-P5 (E622)
AC Adapter 19V / 65W	F5000-P3 (E623)
Active Heatsink + Backplate	F5000-C9
Fanless Heatsink + Backplate	F5000-C10
USB-C Rear Extension Cable (USB 3.1/gen1)	F5000-K8
COM1 extension cable	F5000-K7
Dual WLAN Antenna Kit	tbd
Mono Speaker Kit (for chassis kit)	tbd



Further industrial products offered by Fujitsu

- Connectors
- KVM Switches
- Relays
- Touch Panels
- Thermal Printers
- Wireless Modules



24 Volt Kiosk Printers



Multi-Input Touch Panels

Contact:

Fujitsu Components Europe, B.V.
Tel.: +31 (0)23 556 0910
Fax: +31 (0)23 556 0950
Website: emea.fujitsu.com/components
Address: Diamantlaan 25
2132 WV Hoofddorp
Netherlands

More information

Fujitsu products, solutions & services

Products

www.fujitsu.com/global/products/

In addition to the Fujitsu mainboards, Fujitsu offers a full portfolio of other computing products.

Computing products

- Storage systems: ETERNUS
- Server: PRIMERGY, PRIMEQUEST, Fujitsu SPARC M10, BS2000/OSD Mainframe
- Client Computing Devices: LIFEBOOK, STYLISTIC, ESPRIMO, FUTRO, CELSIUS
- Peripherals: Fujitsu Displays, Accessories
- Software
- Network

Product Support Services with different service levels agreements are recommended to safeguard each product and ensure smooth IT operation.

Solutions

<http://www.fujitsu.com/global/solutions>

The Fujitsu solutions combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships. Fujitsu's Solutions include parts of one or more activity groups (e.g., planning, implementation, support, management, and training services) and are designed to solve a specific business need.

Infrastructure Solutions are customer offerings created by bringing Fujitsu's best products, services and technologies together with those from partners to deliver benefit to our customers' businesses.

Industry Solutions are tailored to meet the needs of specific verticals.

Business and Technology Solutions provide a variety of technologies developed to tackle specific business issues such as security and sustainability, across many verticals.

Services

www.fujitsu.com/global/services/

Several customizable Fujitsu Service offerings ensure that IT makes a real difference and delivers true business value. We do this by leveraging our extensive experience in managing large, complex, transformational IT programs to help clients in planning, delivering and operating IT services in a challenging and changing business environment.

Application Services support the development, integration, testing, deployment and on-going management of both custom developed and packaged applications. The services focus on delivering business and productivity improvements for organizations.

Business Services respond to the challenge of planning, delivering and operating IT in a complex and changing IT environment.

Managed Infrastructure Services enable customers to deliver the optimal IT environment to meet their needs – achieving high levels of IT service quality and performance for data center and end user environments.

Fujitsu green policy innovation

www.fujitsu.com/global/about/environment/

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at:



More information

Learn more about Fujitsu, please contact your Fujitsu sales representative, Fujitsu business partner, or visit our website.

www.fujitsu.com/fts/mainboards/

Copyright

© 2015 Fujitsu Technology Solutions GmbH. Fujitsu and the Fujitsu logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries.

Intel Chipset C236, Xeon C3 and Intel Core i7 / i5 / i3 are trademarks or registered trademarks of Intel Corporation in America and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners. All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Disclaimer

Technical data subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
OEM Mainboard Sales

Email: oem-sales@ts.fujitsu.com

Website: <http://ts.fujitsu.com>
2018-03-21

Copyright © Fujitsu Technology Solutions

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html