


D3713-V/R mITX

Industrial Series



AMD Embedded V1000/R1000 Series SoC Platform for AMD FP5 SoC Processor

- ▶ AMD Radeon™ Vega Graphics (within SoC)
- ▶ Up to 4x DisplayPort V1.4
- ▶ Dual Channel LVDS (24 Bit) and eDP V1.3 (4 k) onboard
- ▶ Designed for Fanless Operation
- ▶ M.2 Key-B & M.2 Key M & Mini-PCI Express® supported

POSSIBILITIES START HERE



D3713-V/R mITX

Industrial Series


The industrial motherboard D3713-V/R mITX supports the AMD Ryzen™ Embedded V1000 and R1000 series processors with integrated AMD Radeon™ Vega Graphics and can be used in applications with high graphical requirements like casino gaming, medical displays, thin clients and industrial PCs.

It is equipped with up to four DisplayPorts, one embedded DisplayPort and one Dual-Channel LVDS (24bit) and powers up to four independent displays in 4K resolution. Depending on how much (graphical) performance is required, there are 5 motherboard versions with different AMD processors available.

PRODUCT HIGHLIGHTS

- ▶ AMD Radeon™ Vega Graphics (within SoC)
- ▶ Up to 4x DisplayPort V1.4
- ▶ Dual Channel LVDS (24Bit) and eDP V1.3 (4k) onboard
- ▶ PCI Express® x4 (Gen3)
- ▶ 8 Bit GPIO & HD Audio onboard
- ▶ USB 2.0 and USB 3.1 (Gen1/Gen2) onboard
- ▶ 2x SATA III; USB Stick Socket
- ▶ Onboard support for 1x M.2 SSD (Key-M: 2230/2242/2280)
- ▶ Onboard support for 1x M.2 (Key-B: 2242/2252/2260/2280)
- ▶ Onboard support for 1x Mini-PCIe (halfsize/fullsize)
- ▶ Dual GbE LAN onboard incl. Teaming Support
- ▶ AMD integrated TPM V2.0 onboard & socket for optional TPM Module

- ▶ WideRange internal/external DC Input (8 V - 36 V)
- ▶ HW Watchdog onboard
- ▶ RS-232/485/422 support onboard



TECHNICAL INFORMATION

SYSTEM	PROCESSOR	AMD Ryzen™ Embedded V1000 / R1000 Series V1: AMD Embedded V1202B SoC V2: AMD Embedded V1605B SoC V4: AMD Embedded V1807B SoC R2: AMD Embedded R1305G SoC R4: AMD Embedded R1606G SoC
	MEMORY	DDR4-3200 SDRAM, Dual Channel 2x SO DIMM sockets, up to 32 GByte memory
VIDEO	GRAPHICS	AMD Radeon™ Vega Graphics Up to 4x DP V1.4 (thereof 2x DP++) 1x embedded DP (eDP V1.4; supporting 4K resolutions) 1x Dual-Channel 24bit LVDS Following max. display combinations are supported: V-Series: 2x DP + 1x LVDS + 1x eDP, 3x DP + 1x LVDS or eDP, 4x DP R-Series: 1x DP + 1x LVDS + 1x eDP, 2x DP + 1x LVDS or eDP, 3x DP
AUDIO	AUDIO CODEC AUDIO INTERFACE	Realtek ALC256 5.1-channel, High Definition Audio Codec
NETWORK CONNECTION	ETHERNET	Intel® i210LM with 10/100/1000 MBit/s, Wake-on-LAN (WoL) by interesting Packets, Link Status Change and Magic Packet™, PXE Support, BIOS MAC Address Display, Teaming Support
PERIPHERAL CONNECTION	USB SERIAL PORT OTHER I/Os	2x USB 2.0 (by header), 2x USB 3.1 Gen1, 2x USB 3.1 Gen1 (by header), 2x USB 3.1 Gen2 1x RS232/422/485; 3x RS232 (2x by header) GPIO (by header)
STORAGE & EXPANSION	SATA PCIe/PCI SLOTS	2x Serial ATA III 600 Interface (up to 6Gbit/s), NCQ, AHCI, 1x M.2 PCIe x2 (Key-M: 2230/2242/2280), 1x Mini PCIe (halfsize/fullsize) PCIe x4: 1x Gen3; 1x M.2 PCIe x4 (Key B: 2242/2252/2260/2280)
POWER	CONNECTOR INPUT VOLTAGE	External/Internal DC-In 8-36 V (DC Jack/4-Pin) DC Input 8 V-36 V (max. 10 A /max. 125 W)

TECHNICAL INFORMATION

FIRMWARE	BIOS	AMI Aptio 5.x (UEFI) BIOS modified and adapted by Fujitsu Technology Solutions; Recovery BIOS, SM-BIOS (DMI), BIOS Update, Quick Boot, Logo Boot, Quiet Boot, Plug & Play, Automatic DRAM Configuration, BIOS Support for S.M.A.R.T., Advanced Power Management, ACPI S3/S4, Wake on time from S5. Boot support for M.2 SSD (AHCI / NVME) BIOS integrated HW Diagnostic Tool, Watchdog Support No legacy OS support, no MBR installation (UEFI only) 2 level HW Watchdog (BIOS Boot/OS) Integrated AMD integrated TPM V2.0 (Socket for optional TPM module prepared)
SYSTEM CONTROL	WATCHDOG REAL TIME CLOCK TPM	
SYSTEM CONTROL	FP HEADER SECURITY	1x Header for Reset button, HDD LED, Power button, Power LED Recovery BIOS, System and BIOS Password, Boot Sequence Control, Serial-/USB-Port Access Protection, Boot Sector Virus Warning, Write Protection for Flash BIOS, EraseDisk (BIOS Feature), AMD integrated TPM V2.0, socket for optional TPM upgrade module
COOLING	FAN	2x PWM fan (CPU/System)
SOFTWARE	OS SUPPORT	MS Windows 10 Linux-64
MECHANICAL	DIMENSIONS (L x W)	Mini-ITX: 6.7" x 6.7" (170 x 170 mm)
CERTIFICATION	EMC & SAFETY	CE Class-B (planned), FCC-B verified (planned) cTUVus acc. IEC62368-1 (planned)

MOTHERBOARD VERSIONS

	PROCESSOR (APU) *)	GRAPHICS RADEON™ VEGA	MAX. MEMORY SPEED
-V1	V1202B Dual-Core 2.3/3.2 GHz **) 15 W/12-25 W TDP ***)	GPU @ 1.0 GHz 3x CU ****) up to 4 displays	DDR4-2400 (ECC supported)
-V2	V1605B Quad-Core 2.0/3.6 GHz **) 15 W/12-25 W TDP ***)	GPU @ 1.1 GHz 8x CU ****) up to 4 displays	DDR4-2400 (ECC supported)
-V4	V1807B Quad-Core 3.35/3.8 GHz **) 45 W/35-54 W TDP ****)	GPU @ 1.3 GHz 11x CU ****) up to 4 displays	DDR4-3200 (ECC supported)
-R2	R1305G Dual-Core 1.5/2.8 GHz **) 8 W/8-10 W TDP ****)	GPU @ 1.0 GHz 3x CU ****) up to 3 displays	DDR4-2400 (ECC supported)
-R4	R1606G Dual-Core 2.6/3.5 GHz **) 15 W/12-25 W TDP ****)	GPU @ 1.2 GHz 3x CU ****) up to 3 displays	DDR4-2400 (ECC supported)

*) 1) APU = Accelerated Processing Unit
**) CPU Base Frequency / Boost Frequency
***) Default TDP / Configurable TDP Range
****) CU = Compute Units

POWER SUPPLY REQUIREMENTS


SOURCE	VOLTAGE RANGE	MIN. PS LOAD	MAX. VOLTAGE TOLERANCE	TYP. MOTHERBOARD INPUT POWER*	MAX. MOTHERBOARD INPUT POWER**
DC-IN (wide range)	8-36 V	0 A	± 5 %	tbd.	125 W (tbd.)

*) Motherboard incl. Memory and M.2 NVME SSD (MS Windows 10 Idle Mode / Full Load)
**) Motherboard incl. Memory, M.2, PCIe/Mini-PCIe devices, USB Devices, LVDS / eDP devices, SATA devices
See upcoming TechNotes document for detailed power requirements


► TECHNICAL INFORMATION

FEATURES	Chipset / SoC 1st DP* / 2nd DP1* / 3rd DP / 4th DP** / LVDS / eDP / HDMI Buzzer / int. Speaker Support (stereo)***/ S.1 Multichannel Audio LAN Gbit / 100 Mbit / 10 Mbit / WoL / PXE / M.2 2230 WLAN-BT**** 2nd LAN Gbit / 100 Mbit / 10 Mbit / WoL / PXE LAN Teaming / LAN DASH Support SATA / SATA RAID / M.2 (SATA) / M.2 (PCIe/NVME) Mini-PCIe / USB 2.0 / USB 3.1 (Gen1) / USB 3.1 (Gen2) FAN monitored & controlled PSU / CPU / AUX1 / AUX2 TEMP monitored CPU / onboard sensors / external sensor	AMD Ryzen™ Embedded + / + / + / (+) / + / + / - + / + / + + / + / + / + / + / - + / + / + / + / + + / - + / - / + / + + / + / + / + - / + / + / - + / + / -
SPECIAL FEATURES	COM interface support for RS-232 / RS-485 / RS-422 Silent Fan / System Guard Recovery BIOS / Desk Update / Multi Boot HDD Password / EraseDisk / TPM V2.0 onboard / optional TPM module BIOS POST- / BIOS Boot- / OS- HW Watchdog Operating Mode 24-7 / 8-5 (hrs per day - days per week) Motherboard operating temperature range (chassis inside)*****	+ + / + + / + / + + / + / + / + - / + / + + / - -10 °C - 70 °C (tbd.)
INTERNAL CONNECTORS	50 DIMM Sockets (DDR4 3200/2400) SATA-III / M.2 Key-M SSD / M.2 Key-B / M.2 2230 WLAN-BT / Mini-PCIe Front Panel Audio (9-Pin, HD Audio) / SP-DIF Out (Digital Audio) USB 2.0 pin header (provides 2 USB channel) / USB Stick socket***** USB 3.1 Gen1 pin header (provides 2 USB channels)***** Serial COM3 header***** / Serial COM4 header***** / Parallel Port header LVDS / LVDS Backlight / Embedded DisplayPort @ 4 lanes FAN PSU / CPU (PWM) / AUX1 (PWM) Intrusion (Case Open) / GPIO (8 Bit) / SMBus (Case Temp.) Stereo Speaker header / DMIC header Front Panel (Power Switch, Reset Switch, LEDs, Intel 10 pin header) SATA Drive Power Connector (5 V/12 V) / DC-In Connector 8-36 V (4 pin)	2 2 / 1 / 1 / - / 1 1 / 1 1 / 1 1 1 / 1 / - 1 / 1 / 1 - / 1 / 1 1 / 1 / - 1 / - 1 1 / 1
EXTERNAL CONNECTORS	DisplayPort V1.4 / HDMI / DVI / VGA Audio Mic. In / Line in / Line out (or driver configuration) LAN (RJ-45) / PS/2 Keyboard / Mouse USB 2.0 / USB 3.1 Gen1 / USB 3.1 Gen2 DC-In connector (external input) 8-36 V @ 10 A max.; lockable Serial COM interface*****	4 (3) / - / - / - - / 1 / 1 2 / - / - 0 / 2 / 2 1 2

*) Supports DP++
 **) V-series only
 ***) Stereo speaker support; 2 W @4Ω
 ****) M.2 WLAN possible via Mini-PCIe to M.2 converter module D3436-5
 *****) Forced cooling required for high operating temperature range. See upcoming TechNotes document for details
 *****) USB 3.1 Gen1 or USB 2.0 (depends on DisplayPort #3 setting; USB2.0 for 4k resolution on DP #3; BIOS Setup option);
 *****) USB3 connector includes separate USB2.0 signal pins (2 channels)
 *****) COM3 / COM4
 *****) RS-232 @ reduced feature set / pin count; see upcoming TechNotes document for details



► CONNECTOR / SOCKET DIAGRAM



▶ ORDERING INFORMATION

ARTICLE	PART NO.	DESCRIPTION
D3713-V1 mITX		AMD Embedded V1202B SoC
D3713-V2 mITX		AMD Embedded V1605B SoC
D3713-V4 mITX		AMD Embedded V1807B SoC
D3713-R2 mITX		AMD Embedded R1305G SoC
D3713-R4 mITX		AMD Embedded R1606G SoC
ACCESSORIES		
ACTIVE HEATSINK + BACKPLATE	F5000-Cx	
FANLESS HEATSINK + BACKPLATE	F5000-Cy	Fullsize slot bracket
USB-C REAR EXTENSION CABLE	F5000-K8	USB 3.1 Gen1 (fits to IO-shield)
RISERCARD	F5000-R6	1x PCIe X4
SERIAL PORT CABLE	F5000-K10	400 mm, fullsize slot bracket
MINI PCIE TO M.2 ADAPTER	F5000-M3	

▶ Global Headquarters

Kontron S&T AG

Lise-Meitner-Str. 3-5
 86156 Augsburg, Germany
 Tel.: + 49 821 4086 0
 Fax: + 49 821 4086 111
 info@kontron.com
www.kontron.com