

	ELO	Impact
Diagonal size	21.5"	21.5"
Aspect ratio	16:9	16:9
Model name	2293L、2294L aka ELO p/n E330620	21.5" promo monitor with PCAP touch
Dimensions	516mm×311mm×37.9mm	516mm×311mm×37.9mm
Controler IC	EETI	EETI
Number of touches	10-touch	10-touch
Brightness (panel)	250nits	250nits
Contrast ratio	1000:1	3000:1
Viewing angle	2293L: 85°/80°or 170°/160° 2294L: 89°/89°or 178°/178°	89°/89°or 178°/178°
Native resolution	1920×1080 @ 60Hz	1920×1080 @ 60Hz
Video Interface	VGA+HDMI+DP	VGA+HDMI+DP
Input power	12 VDC±5%	12 VDC±5%
DC barrel plug	2.1mm pin inner diameter 5.5mm barrel outer diameter	2.1mm pin inner diameter 5.5mm barrel outer diameter
OSD	External, Control: Power, Select, Up, Down, Menu	External, Control: Power, Auto, Up, Down, Menu
Light sensor	NA	Optional
Mounting options	VESA 4-hole 100mm mounting interface on rear of unit; 2-hole mounting interface on all 4 sides; Flush mount with included brackets	VESA 4-hole 100mm mounting interface on rear of unit; 2-hole mounting interface on all 4 sides; Flush mount with included brackets
Temperature	Operating:0℃~40℃ (32°F~104°F) Storage:-20℃~60℃ (-4°F~140°F)	Operating:0℃~40℃ (32°F~104°F) Storage:-20℃~60℃ (-4°F~140°F)
Humidity	Operating:20%~80% Storage:10%~95%	Operating:20%~80% Storage:10%~95%
Agency Approvals	UL,CE,FCC,CCC,KCC,VCCI,TUV, cUL,Rohs	UL,CE,FCC,CCC,Rohs
MTBF	50,000 hours demonstrated	50,000 hours demonstrated