

	ELO	Impact
Diagonal size	27"	27"
Aspect ratio	16:9	16:9
Model name	2794L aka ELO p/n E707022	27" promo monitor with PCAP touch
Dimensions	644.2mm×388.4mm×39.6mm	644.2mm×388.4mm×39.6mm
Controler IC	EETI	EETI
Number of touches	10-touch	10-touch
Brightness (Panel)	300nits	300nits
Contrast ratio	3000:1	3000:1
Viewing angle	89°/89°or 178°/178°	89°/89°or 178°/178°
Native resolution	1920×1080 @ 60Hz	1920×1080 @ 60Hz
Video Interface	VGA+HDMI+DP	VGA+HDMI+DP
Input power	12 VDC±5%	12 VDC±5%
DC barrel plug	2.1mm pin inner diameter 5.5mm barrel outer diameter	2.1mm pin inner diameter 5.5mm barrel outer diameter
OSD	External, Control:Power, Select, Up, Down, Menu	External, Control:Power, Auto, Up, Down, Menu
Light sensor	NA	Optional
Mounting options	200×100mm VESA mount on rear of unit; 4-hole mounting interface on all 4 sides; Flush mount with included brackets	200×100mm VESA mount on rear of unit; 4-hole mounting interface on all 4 sides; Flush mount with included brackets
Temperature	Operating:0℃~40℃ (32℉~104℉) Storage:-20℃~60℃ (-4℉~140℉)	Operating:0℃~40℃ (32℉~104℉) Storage:-20℃~60℃ (-4℉~140℉)
Humidity	Operating:20%~80% Storage:10%~95%	Operating:20%~80% Storage:10%~95%
Agency Approvals	UL,CE,FCC,CCC,KCC,VCCI,TUV, cUL,Rohs	UL,CE,FCC,CCC,Rohs
MTBF	50,000 hours demonstrated	50,000 hours demonstrated