



- 15.6" Full Screen Android Touch AIO
- Support Android 10.0
- Multi-touch Interactive Experience
- Commercial-Grade Performance
- Multiple Connections for Different Industries

PC Parameters	Processor	Rockchip RK3399 processor (choose Dual-core Cortex-A72 up to 1.8GHz, or Quad-core Cortex-A53 up to 1.4GHz), with Mali-T864 GPU
	Memory	4GB DDR3
	Storage	32GB EMMC
	Operating System	Android 10.0
	Touch Technology	P-CAP
	Touch Point	10
	Display Technology	Active Matrix TFT-LCD With LED Backlight
LCD Panel Parameters	Aspect Ratio	16 9
	Active Display Area (W xH)	344.16 (H) x 193.59 (V) mm
	Native Resolution	1920×1080@60Hz
	Response Time (Typ.)	25ms
	Display Colors	262K
	Luminance (Typ.)	250nits; with P-Cap 210nits
	Contrast Ratio (Typ.)	1000:1
	Viewing Angle (Typ.)	left/right : 178 (89/89) up/down : 178 (89/89)
	LAN	1 x RJ45 (10/100Mbps/1Gbps) POE(≤30W)
I / O Port	WLAN	WIFI & Bluetooth
	USB Port	4xMicro USB2.0, 1 xUSB3.0
	VGA/HDMI/DP (Display) Port	1xHDMI out
	Video	NA
	COM Port	NA
	Power In	1x12V DC Jet ϕ 2.5
	Case/Bezel Color	Black
Overall Parameters	Mounting Options	VESA : 75 x 75mm, 100 x 100mm
	Outline Dimension (W×H×D)	368.8 x 218.2 x 28.5mm
		External Adapter: 100-240 VAC, 50-60 Hz
	Webcam	Input Voltage Range: +12VDC \pm 5% NA
	Speaker	2x2W
	Power Consumption	MAX :30W
	Operating Altitude	≤3000m
	Temperature	Operating: 0°C to 50°C, storage: -20°C to 60°C
	Humidity (non-condensing)	Operating: 20% to 80%, storage: 10% to 90%
	Accessories	60W Adapter
	Weight	Net: 3.1kg Gross: 4.5kg
	MTBF	30,000 hours demonstrated
	Agency Approvals	FCC, CE, UL, BIS, CCC, GMS
	Warranty	2 years