



- 21.5" Full Screen Android Touch AIO
- Support Android 10.0
- Multi-touch Interactive Experience
- Commercial-Grade Performance
- Multiple Connections for Different Industries

<b>PC Parameters</b>	Processor	Rockchip RK3399 processor (choose Dual-core Cortex-A72 up to 1.8GHz, or Quad-core Cortex-A53 up to 1.4GHz), with Mali-T864 GPU
	Memory	4GB DDR3
	Storage	32GB EMMC
	Operating System	Android 10.0
	Touch Technology	P-CAP
	Touch Point	10
	Display Technology	Active Matrix TFT-LCD With LED Backlight
<b>LCD Panel Parameters</b>	Aspect Ratio	16 9
	Active Display Area (W x H)	476.64(H) x 268.11(V) mm
	Native Resolution	1920×1080@60Hz
	Response Time (Typ.)	25ms
	Display Colors	16.7M
	Luminance (Typ.)	250nits; with P-Cap 210nits
	Contrast Ratio (Typ.)	3000 : 1
	Viewing Angle (Typ.)	left/right : 178 (89/89) up/down : 178 (89/89)
	LAN	1 x RJ45 (10/100Mbps/1Gbps) POE(≤30W)
<b>I / O Port</b>	WLAN	WIFI +Bluetooth
	USB Port	4 x Micro USB2.0, 1 x USB3.0
	VGA/HDMI/DP (Display) Port	1 x HDMI out
	Video	NA
	COM Port	NA
	Power In	1 x 12V DC Jet € 2.5
	Case/Bezel Color	Black
<b>Overall Parameters</b>	Mounting Options	VESA : 75 x 75mm, 100 x 100mm
	Outline Dimension (W×H×D)	505.2 x 296.8 x 36.8mm
		External Adapter: 100-240 VAC, 50-60 Hz
	Webcam	Input Voltage Range: +12VDC ± NA
	Speaker	2x2W
	Power Consumption	MAX :30W
	Operating Altitude	≤3000m
	Temperature	Operating: 0°C to 50°C, storage: -20°C to 60°C
	Humidity (non-condensing)	Operating: 20% to 80%, storage: 10% to 90%
	Accessories	60W Adapter
	Weight	Net: 4.3kg Gross: 5.2kg
	Carton Box Dimensions	670 x 490 x 200mm
	MTBF	30,000 hours demonstrated
	Agency Approvals	FCC, CE, UL, BIS, CCC, GMS
	Warranty	2 years