

SPECIFICATIONS

Name	23.8 Inch LED-Framed Double-sided Monitor
Model	IC24DS-SL
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	527.04 × 296.46mm
Native Resolution	1920 × 1080@60Hz
Response Time (Typ.)	14ms
Display Colors	16.7M
Luminance (Typ.)	250nits
Contrast Ratio (Typ.)	1000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
Screen Parameters	
Surface Treatment	Tempered or Chemically Strengthened
Thickness (Total)	2.0
Light Transmission	≥90%
Overall Parameters	
Case/Bezel Color	Black
Mounting Options	Pole + Quick Mount Bracket, portrait mode
Outline Dimensions (W×H×D)	829.5mm × 350.1mm × 40.0mm
Power Supply	Input Voltage Range: +12VDC ± 5%
On Screen Display (OSD)	Control (remote): Power, Auto, Up, Down, Menu
Power Consumption (Max.)	90W
Operating Altitude	≤ 3000m

Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	HDMI, HDMI, DP, USB (Type B)
Accessories	Optional
Carton Box Dimensions (1 unit in one carton)	780mm (L) × 470mm (W) × 240mm (H)
Weight	Net: TBD kg Gross: TBD kg
MTBF	50,000 hours demonstrated
LED Lights Color	Multicolor
LED Lights Location	4 LED lights bar (Front & Edge)
LED Controller	Built-in
Agency Approvals	CE, FCC
Warranty	3 years

Ordering Information		
Model	Part Number	Description
OML24D-R02000-0D2F40-2.1181A		23.8", 16:9, 250nits, non-touch, LED-framed double-sided monitor, LED lights location front & edge, portrait mode

Optional Accessories		
Model	Part Number	Description
USB Cable	130300224R	USB Cable, 1500mm, male to male
HDMI Cable	130300881R	1500mm
DP Cable	130300932R	1500mm
Adaptor	130104010R	Power Adapter 12V/90W/2.5mm/1200mm
Power Cable		1500mm

Add: 6010 Cornerstone Ct. San Diego, Ca 92121
 Tel: 858-634-4800
 Website: www.impactcomponents.com

For more information, contact sales@impactcomponents.com